

TRANSMITTAL - NATIONAL PARK SERVICE

Park: Florissant Fossil Beds N.M. Project: Water System Contract No.: C157410C023 TO P12PDD11095 Transmittal No.: 12 Sheet: 1 of 1 Date: 8/3/13

Contractor: Bairco Construction, Inc. Subcontractor/Supplier: NPS ACTION

Item No.	Specification Section No.	Paragraph No.	Description of Item (Size, Type, Name, Manufacturer, Use, Etc.)	No. of Copies Submitted	No. of Copies Returned	Approved	Approved with Notations	Disapproved - Resubmit
1	061600	2.1 A	Plywood: Treated Exterior Rated CDX	2				
2								
3								
4								
5								
6								

Contractor Signature: [Signature] Recommended by: [Signature]


Title: Project Manager Date: 8/3/13 Title: [Blank] Date: [Blank]

I hereby certify that this submittal has been reviewed for accuracy, completeness, and compliance with contract requirements (FAR 52.236-21)

Review Comments: [Blank] Action By: [Blank] Date: [Blank]

Approval of this submittal is subject to the provisions of the contract drawings and specifications. This action is for general concurrence only and the Government is not responsible for errors or omission.

SUBMITTAL LOG DATES: From contractor [Blank] To reviewer [Blank] From reviewer [Blank] To Contractor [Blank] Distribution: () Contractor () DSC File () COR () A/E () DSC Interim () COR Interim () Contractor Interim CM-16Rev 4/00 (Formerly DSC-1(CS))



McFarland Cascade
The Outdoor Projects People

PERMANENT WOOD FOUNDATION

LUMBER

Size	Pcs/Unit	8'	10'	12'	14'	16'	18'	20'
2x4	156	✓		✓		✓		
2x6	96	✓		✓		✓		
2x8	72	✓		✓		✓		
2x10	40					✓		
2x12	32					✓		

PLYWOOD 4x8

Size	Type	Pcs/Unit
1/2"	CDX	66
1/2"	CDX P&TS	66
5/8"	CDX	52
5/8"	CDX P&TS	52
3/4"	CDX	44
3/4"	CDX P&TS	44
7/8"	FF T&G Udl	44
1 1/8"	FF T&G Udl	30

LUMBER DESCRIPTION

- 2x4 Std&Btr S4S KD HF
- 2x6 through 2x12, 2&Btr S4S DK HF
- Plywood is per above grade specifications (P&TS is plug & touch sanded)

PLYWOOD DESCRIPTION

- As noted. P&TS is plug and touch sanded. FF Udl. is full faced underlayment

TREATMENT

- Lumber is incised and treated to AWPA C1, C22 (FDN) Standard which calls for .60 CCA-C treatment, kiln dried after treatment, and paper wrapped
- With the exception of incising, plywood is treated the same
- Each piece bears specification stamp
- Natural CCA green color

INTENDED USE

- Used in lieu of concrete to construct foundations. Can be used for any number of construction purposes where structural members and sheathing come in contact with the ground, such as mobile home skirting.

SAFETY AND HANDLING

- See EPA-approved Consumer Information Sheet prior to use
- Use hot-dipped galvanized or rust resistant screws for best results

McFarland Cascade, P.O. Box 1496, Tacoma, WA 98401
(253)572-3033 • (800)426-8430 • FAX: (253)272-1398